

Name A H Date Jan 2013 Truck / City WCRC Event Reedy

### Front Suspension

4.8mm Ball Stud:  UM128 (Std)  UMW508 (+2mm High Mount)

Camber: .5°

Upper Spacer: 2 mm

4.8mm Ball Stud Spacer: .5 mm

Axle Spacer:  Out 1 mm  In 2 mm

Wheel Hub: Std mm

4.8mm Ball Stud:  LA246 (-1mm Low Mount)  97050M (Std)

Ackerman Steer Spacer: 0 mm

Bump Steer Spacer:      mm

Toe:  In  Out 1°

Tie Rod:     

Front Bulkhead Weight Placement:  None  Bulkhead Inside      oz      g  On the skid plate      oz      g \* 1oz=28g

Caster:  25°  30°  A (UM502)  B (UM721/Std.)  C (UM567)

Spacer:  0.5  1.0  None

Caster Block:  0°  2°  4°

Caster Block position:  IN (wide/Std)  OUT (Narrow)

Axle Height Spacer:  1 mm  .5 mm

Wheelbase: F: 1 mm R: 0 mm

Comments:     

### Rear Suspension

Sus Holder Spacer: F  0.5  1.0  None R  0.5  1.0  None

Anti-Squat: 2°

4.8mm Ball Stud:  UM129  UMW508 (+2mm High Mount)  97050M  UM128 (Std)

Sway Bar:  None       mm

Upper Spacer: 2.5 mm

Lower Sus Holder:  Normal  Aluminum(Opt)  RF  UMW511+UMW512  Wide  RF2  UMW514+UMW515

Universal Swing Shaft:  Type-B (UM519)  Type-B2 (UM519-2)

Camber: 1°

Upper Spacer: .5 mm

Wheelbase: F: 0 mm R: 2 mm

Wheelbase: F:      mm R:      mm

Rear Hub add Toe:  0°Type-B (UM519)  0°Type-B2 (UM519-2)  0°Alu (UMW516-0)  0.5°Alu (UMW516-05)  1°Alu (UMW516-1)

Axle Spacer:  Out .3 mm  In      mm

Motor Position:  Rear Motor  Midship Motor

Diff.:  Gear Diff. #       Ball Diff.

Comments: UM521-1 arms

### Shock

Shock Piston: Front Stock Rear Stock

Shock Oil: # 30 # 25

Shock Spring: Avid Yellow XGS015

Limiters: in mm out mm in mm out mm

Shock Length(A):      mm      mm

Shock Length(B): 19 mm 27 mm

O-ring: ORG03X ORG03X

Ball End type: Front: S  M  L  Rear: S  M  L

### Battery Placement:

None  Screw

Front Rear

Foam:  Front  Rear  None

### Chassis

F 24 mm Ride Height: R 23.5 mm

### Tire

Front Rear Traction Compound or comment:

Tire: Hand Out

Inserts: Hand Out

Wheel: Stock Stock

### Comment

PL Bulldog body and JC wing. Avid Triad slipper

### Truck Condition

- Smooth
- Bumpy
- Low Traction
- Med. Traction
- High Traction
- Wet
- Dry
- Sandy
- Soft Dirt
- Grass
- Blue Groove
- Clay
- Dusty
- Other

### Wing

- Blast-S
- Blast-L
- Step-S
- Step-M
- Step-L
- Step 2.0
- Lip:
- Wing Mount:  Narrow  Wide
- Wing Angle:  4°  7°  10°