

Name: **Jared Tebo** Date: **9/25/2013** Truck / City: **Silver Dollar/ Chico, CA** Event: **IFMAR Worlds**

Front Suspension

***Arrow points toward rear.**

4.8mm Ball Stud: Camber: **1.5°**

UM128 (Std) UMW508 (+2mm High Mount)

Upper Spacer: **1** mm

4.8mm Ball Stud Spacer: **1** mm

Axle Spacer: Out **1** mm In **2** mm

Wheel Hub: ___ mm

4.8mm Ball Stud: LA246 (-1mm Low Mount) UM129 (Std)

Ackerman Steer Spacer: **0** mm

Bump Steer Spacer: **0** mm

Toe: In Out **0°**

Front Bulkhead Weight Placement: None Bulkhead Inside ___ oz ___ g On the skid plate ___ oz ___ g * 1oz=28g

Caster: 25° 30° A (UM502) B (UM721/Std.) C (UM567)

Spacer: 0.5 1.0 None

Caster Block: 0° 2° 4°

Block position: IN OUT

Axle Height Spacer: ___ mm **1.5** mm

Comments: **Ackerman reversed*** Wheelbase: F: **1** mm R: **0** mm

Rear Suspension

Sus Holder Spacer: F 0.5 1.0 None R 0.5 1.0 None

Anti-Squat: **0°**

Upper Spacer: **1** mm

Wheelbase: F: **1** mm R: **1** mm

4.8mm Ball Stud: UM129 (Std) UMW508 (+2mm High Mount) 97050M

Sway Bar: None ___ mm

Camber: **1.5°**

Wheelbase: F: ___ mm R: ___ mm

Rear Hub add Toe: 0° Type-B (UM519) 0° Type-B2 (UM519-2) 0° Alu (UMW516-0) 0.5° Alu (UMW516-05) 1° Alu (UMW516-1)

Axle Spacer: Out ___ mm In ___ mm

RR: RR Mid

Lower Sus Holder: Normal RF Aluminum(Opt) UMW511+UMW512 Wide RF2 UMW514+UMW515

Comments: **UMW705/707-A/B Out UM521-1 Used**

Motor Position

Rear Motor Midship Motor

Diff.

Gear Diff. # **5000** Ball Diff.

Shock

Shock Piston:	Front 3X1.4	Rear 2X1.6
Shock Oil:	# 32.5	# 27.5
Shock Spring:	Pink	Gold
Limiters:	in out mm mm	in out mm mm
Shock Length(A):	___ mm	___ mm
Shock Length(B):	20 mm	27 mm
Shock Length(C):	___ mm	___ mm
Ball End type:	Front: <input type="checkbox"/> S <input checked="" type="checkbox"/> M <input type="checkbox"/> L	Rear: <input type="checkbox"/> S <input checked="" type="checkbox"/> M <input type="checkbox"/> L

Chassis

Screw:

Ride Height: F **24** mm R **23** mm

Battery Position

Battery Type: Straight Separate Short

Battery Placement: Front Rear

Tire

Front: **AKA 3 Rib M PL Suburb**

Rear: **AKA 3 Rib M PL Suburb**

Inserts: **AKA Red** **PL White**

Wheel: **AKA** **AKA**

Traction Compound: ___

Electronics

Motor: **Orion VST2 7.5**

Pinion/Spur: ___

Battery: ___

ESC: **Orion R10 Pro**

Truck Condition

Smooth Sandy Bumpy Soft Dirt Low Truction Grass Med. Truction Blue Groove Higt Truction Clay Wet Dusty Dry Other

Wing

Blast-S Wing Mount: Narrow Wide

Blast-L Step-S Step-M Step-L Step 2.0

Wing Angle: 4° 7° 10°

Lip: **1**

Comment

Full Titanium Screws
Servo / Battery / ESC
Receiver and Capacitor/switch on opposite sides