

Name Jared Tebo Date Oct. 2013 Truck / City Hot Rod Hobbies Event Reedy Truck Race

Front Suspension

Upper Spacer: 1 mm

4.8mm Ball Stud: UM128 (Std) UMW508 (+2mm High Mount)

Shock Mount: IN OUT

Camber: 1.5°

Ackerman Steer Spacer: 0 mm

4.8mm Ball Stud: LA246 (-1mm Low Mount) UM129 (Std)

Bump Steer Spacer: 0 mm

Toe: In Out 0°

Front Bulkhead Weight Placement:
 None
 Bulkhead Inside 10 oz g
 On the skid plate 10 oz g * 1oz=28g

Caster Spacer: 25° 30° 0.5 1.0 None

Comments: UMW522 F plate **Wheelbase:** Long Middle Short

Axle Spacer: Out _____ mm In _____ mm

Axle Height Spacer: Up _____ mm Down _____ mm

Rear Suspension

Sus Holder Spacer: F 0.5 1.0 None R 0.5 1.0 None

Anti-Squat: 0°

Upper Spacer: 2 mm

Wheelbase: F: 3 mm R: 3 mm

4.8mm Ball Stud: UM128 (Std) UMW508 (+2mm High Mount)

Sway Bar: None _____ mm

Camber: 2°

Rear Hub add Toe: 0°Type-B (UM519) 0°Type-B2 (UM519-2) 0°Alu (UMW516-0) 0.5°Alu (UMW516-05) 1°Alu (UMW516-1)

Lower Sus Holder: Normal RF Aluminum(Opt) UMW511+UMW512
 Narrow RF2 UMW514+UMW515

Upper Spacer: 2 mm

Axle Spacer: Out _____ mm In _____ mm

Diff.
 Gear Diff. # 5000
 Ball Diff.

Shock

	Front	Rear
Shock Piston:	<u>Std 5h</u>	<u>Std 5h</u>
Shock Oil:	# <u>37.5</u>	# <u>32.5</u>
Shock Spring:	<u>Orange</u>	<u>Red</u>
Limiters:	in _____ mm out _____ mm	in _____ mm out _____ mm
Shock Length(A):	<u>27</u> mm	<u>33</u> mm
Shock Top Type:	<input type="checkbox"/> Std:RB5 <input type="checkbox"/> Low:SC	<input type="checkbox"/> Std:RB5 <input type="checkbox"/> Low:SC
5.8mm Ball End:	Front: <input checked="" type="checkbox"/> S <input type="checkbox"/> M <input type="checkbox"/> L	Rear: <input checked="" type="checkbox"/> S <input type="checkbox"/> M <input type="checkbox"/> L

Body / Wing / Chassis

Wing: _____ **Body:** _____

Lip high: _____ **Battery Placement:** Front Rear

Battery Post: Pla Alu

Weight Placement: * 1oz=28g

Ride Height: F 31 mm R 27 mm

Tire

	Front	Rear
Tire:	<u>AKA Slingshot</u>	<u>AKA Slingshot</u>
Inserts:	<u>AKA Bik</u>	<u>AKA Bik</u>
Wheel:	<u>AKA</u>	<u>AKA</u>
Traction Compound:	<u>Soft Compound Tires</u>	

Truck Condition

- | | |
|--|---|
| <input checked="" type="checkbox"/> Smooth | <input type="checkbox"/> Sandy |
| <input type="checkbox"/> Bumpy | <input type="checkbox"/> Soft Dirt |
| <input type="checkbox"/> Low Truaction | <input type="checkbox"/> Grass |
| <input type="checkbox"/> Med. Truaction | <input checked="" type="checkbox"/> Blue Groore |
| <input checked="" type="checkbox"/> Higt Truaction | <input type="checkbox"/> Clay |
| <input type="checkbox"/> Wet | <input type="checkbox"/> Dusty |
| <input checked="" type="checkbox"/> Dry | <input type="checkbox"/> Other |

Kind in spring:

Soft ↑ Hard ↓	Red
	Yellow
	Orange

Comment : One brass weight in battery.

Electronics

Motor: Orion VST2 6.5
 Pinion/Spur: 17/82
 Battery: Orion WTS
 ESC: Orion R10 Pro
 Radio: KO Propo EX10
 Servo: KO RSXResponse
 Throttle/Brake: _____
 EPA: _____ Expo: _____
 Initial brake: _____
 Drag brake: _____
 Throttle profile: _____
 Steering expo: _____
 Steering speed: _____