

Name Jared Tebo Date January 2010 Truck / City CRCRC Event 2010 CRCRC Winter Elec. Champs

Front Suspension

Shock Stay
 Std (UM511)
 C-Comp (UMW500)

Upper Spacer 1 mm

4.8mm Ball Stud
 Standard (UM128)
 High Mount (+2mm:UMW508)

Axle Type
 Standard (Steel:UM506)
 Option (Aluminum:UMW507)

Ackerman Steer Spacer 0 mm

Bump Steer Spacer 0 mm

Axle Spacer
 Out (Standard) _____ mm
 In _____ mm

Axle Height Spacer
 Up
 Down

Camber + - 2 °

Caster
 25°
 30°

Spacer
 0.5
 1.0
 None

Toe In Out 0 °

Front Bulkhead Weight Placement
 None
 Bulkhead Inside _____ oz 10 g
 On the skid plate _____ oz 10 g * 1oz=28g

Comments: Caster block spaced middle. 10g. Above Achorman

Rear Suspension

Lower Sus Holder
 Normal RF:RB5 Aluminum(Opt) UMW511+UMW512
 Wide RF2:RB5SP UMW514+UMW515

Sus Holder Spacer
 F 0.5 1.0 None
 R 0.5 1.0 None

Anti-Squat _____ °

Swing Shaft
 62.5mm:RB5 (UM510, UM510-01)
 65.5mm:RB5SP (UM522, LA232-01)

Upper Spacer 2 mm

Wheelbase
 Long
 Middle
 Short

Rear Hub add Toe
 0° (Standard)
 0.5° (LA244-05)

Sway Bar None
 _____ mm

Wing Height
 1
 2
 3

Shock Stay
 Std:RB5 (UM512)
 Std C-Comp:RB5-opt (UMW501)
 Short:RB5SP (UM520)

Upper Spacer 2 mm

Lower Arm
 Short:RB5 (UM503)
 Middle:RB5SP (UM521)

Wheel Shaft Type
 RB5SP (UM522-02)
 RB5 (UM510-02)
 for PL-Wheel (UMW502)

Wheel Spacer _____ mm
 Type-B (UM519)
 Up (LA244-05)
 Middle
 Down

Axle Spacer
 Out _____ mm
 In _____ mm

Camber + - 1 °

Comments: New rear arms with one hole. New rear hub with longer camber holes

Shock

	Front	Rear
Shock Piston	3 - B	3 - B
Shock Oil	#32 1/2 Losi	#27 1/2 Losi
Shock Spring	Orange #55	Silver #70
Limiters	in _____ mm	in _____ mm
	out _____ mm	out _____ mm
Shock Length (A)	2 Turns _____ mm	4 Turns _____ mm
Shaft Length (B)	_____ mm	1mm Limiter mm
Shock Top Type	<input checked="" type="checkbox"/> <input type="checkbox"/> <input type="checkbox"/>	<input checked="" type="checkbox"/> <input type="checkbox"/> <input type="checkbox"/>
Rear Shock Body	<input checked="" type="checkbox"/> Short:RB5SP (W5196-01V) 38mm	<input type="checkbox"/> STD:RB5 (W5187-01V) 42mm
	<input checked="" type="checkbox"/> STD:RB5SP (W5193-01) 50mm	<input type="checkbox"/> Opt:ZX5 (W5183-02) 54mm
Rear Shock Shaft	<input type="checkbox"/> Opt:ZX5 (W5183-02) 54mm	

Body / Wing / Chassis

Wing
 Aquarius (LA239)
 Sagittarius (LA240)
 Aries (LA241)
 Blast-L (LA251)
 Step-L (LA247)
 Step-S (LA247)
 Blast-S (LA247)
 Other: _____

Body
 Trident:RB5 (UMB01)
 Sword:RB5SP (UMB02)
 Other: _____

Battery Placement
 Front Rear

Wing Angle
 4° 7° 10°

Weight Placement * 1oz=28g

 Ride Height A B F 24 mm R 23 mm

Truck Condition

<input checked="" type="checkbox"/> Smooth	<input type="checkbox"/> Sandy
<input type="checkbox"/> Bumpy	<input type="checkbox"/> Soft Dirt
<input type="checkbox"/> Low Truction	<input type="checkbox"/> Grass
<input type="checkbox"/> Med. Truction	<input type="checkbox"/> Blue Groove
<input checked="" type="checkbox"/> Higt Truction	<input checked="" type="checkbox"/> Clay
<input checked="" type="checkbox"/> Wet	<input type="checkbox"/> Dusty
<input type="checkbox"/> Dry	<input type="checkbox"/> Other

Kind in spring

#55	Orange
#60	Orange Yellow
#65	Yellow
#68	Blue
#70	Silver
#72	Cobalt blue
#75	Light Green
#80	Green

Tire

	Front	Rear
Tire	Pink 7202 Slick	Taper Slick
Inserts	JC And 1	JC And 1
Wheel	Kyosho	Kyosho
Traction Compound	Zip Grip	

Others

gear ratio = 2.6

Motor Orion 7.5

Pinion/Spur _____ / _____

Battery Orion 4600

ESC Orion

Comment : Total Weith: 1521g
 Battery Weight 265g