

Name Jared Tebo Date Jan 2013 Truck Ohio RC Factory Event CRCRC Midwest Champs

Front Suspension

Shock stay hight: .5 mm

Spacer: 0 mm

Shock Stay: LA216B(SP) LA216HB

Ride Height: 20.5 mm

Camber Angle: -1 °

Toe Angle: 0 °

Sway Bar: none

Front Diff: Rigid Oneway Differential, Setting: loose

Bump Steer Spacer: 0 mm **LA246 low mount**

Caster Block: 7° 10°

Sus. Holder Spacer: Front Rear

Axle-Height Spacer: Up Down

Bellcrank Spacer: 0 mm

Rear Suspension

Shock stay hight: 0 mm

Spacer: 1 mm

Shock Stay: LA217(SP) LA217H

Wing Height: 1 mm

Camber Angle: -1 °

Sway Bar: 1.2

Sus. Holder(RF): IN OUT A

Sus. Holder(RR): IN OUT E

Ride Height: 20.5 mm

Sus. Holder Spacer: Front Rear

Wheel Spacer: mm

Rear Hub add Toe: 0° Type-B(UM519) 0° Type-B2(UM516-2) 0° Alu(UMW516-0) 0.5° Alu(UMW516-05) 1° Alu(UMW516-1)

Rear Sus. Arm: LA272(UM566,UM521)(SP) UM521-1(1-Hole) LA255

Hub Spacer: F: 0 mm R: 2 mm

Shock

	Front	Rear
Shock Piston:	<u>5 hole</u>	<u>5 hole</u>
Shock Oil:	<u># 37.5</u>	<u># 27.5</u>
Shock Spring:	<u>Yellow</u>	<u>Gold</u>
Limiters:	in <u>1</u> mm out <u> </u> mm	in <u>2.75</u> mm out <u> </u> mm
Shock Length(A):	<u>19</u> mm	<u>25.5</u> mm
Shock Top Type:	<input type="checkbox"/> <input type="checkbox"/> <input type="checkbox"/> <input type="checkbox"/>	<input type="checkbox"/> <input type="checkbox"/>
	UM719 Std:RB5 Low:ZX5FS Std:RB5 Low:ZX5FS	
5.8mm Ball End:	Front: <input type="checkbox"/> S <input checked="" type="checkbox"/> M <input type="checkbox"/> L	Rear: <input type="checkbox"/> S <input checked="" type="checkbox"/> M <input type="checkbox"/> L

Tire

	Front	Rear
Tire:	<u>AKA Vektor Clay</u>	<u>Handlebar Clay</u>
Inserts:	<u>AKA Red</u>	<u>AKA Red</u>
Wheel:	<u>AKA</u>	<u>AKA</u>
Traction Compound:	<u>Buggy Grip</u>	

Body/Wing/Other

Body: PL Bulldog

Wing: Step 2.0

Lip hight: 20 mm

Wing Angle: 4° 7° 10°

Battery Post: Pla Alu

Slipper Type: Direct Separates

Slipper Sheet(F-R): Red-White Red-Red White-White

Center Post: Pla Alu

Back bone screw: F R

Electronics

Motor: Orion 6.5

Pinion/Spur: 18/78

Battery: Orion 5500

ESC: Orion R10 Pro

Radio: KO Propo

Servo: KO RSx One10

Throttle/Brake:

EPA: 100/90 Expo:

Initial brake: 0

Drag brake: 0

Throttle profile: 4

Steering expo:

Steering speed:

Kind in spring

Soft ↑	<u>Pink</u>
	<u>White</u>
	<u>Gold</u>
	<u>Red</u>
	<u>Yellow</u>
	<u>Orange</u>
Hard ↓	<u>Green</u>

Sway Bar

<u>1.0</u>	<u>White</u>
<u>1.1</u>	<u>Pink</u>
<u>1.2</u>	<u>Red</u>
<u>1.3</u>	<u>Orange</u>
<u>1.4</u>	<u>Yellow</u>
<u>1.5</u>	<u>Blue</u>
<u>1.6</u>	<u>Green</u>

Comments

F and R arms 2mm short

Carbon Top Deck LAW44

40g weight in rear

<input checked="" type="checkbox"/> Smooth	<input type="checkbox"/> Sandy
<input type="checkbox"/> Bumpy	<input type="checkbox"/> Soft Dirt
<input type="checkbox"/> Low Truction	<input type="checkbox"/> Grass
<input type="checkbox"/> Med. Truction	<input checked="" type="checkbox"/> wet
<input checked="" type="checkbox"/> Higt Truction	<input type="checkbox"/> Dry
<input type="checkbox"/> Blue Groore	<input type="checkbox"/> Dusty
<input checked="" type="checkbox"/> Clay	<input type="checkbox"/> Other