

Name Kohta Akimoto Date 28/OCT/2011 Track Yatabe Arena Event _____

Front Suspension

Shock stay high: 0 mm
 Spacer: 0.75 mm
 Shock Stay:
 LA216B(SP)
 LA216HB

Ride Height: 20.5 mm
 Bump Steer Spacer: 0 mm
 Caster Block:
 7°
 10°
 Axle-Height Spacer: Up Down

Gamber Angle: 1 °
 Toe Angle: -1 °
 Sway Bar: None
 Front Diff:
 Rigid
 Oneway
 Differential, Setting: Soft

Sus. Holder Spacer:
 Front
 Rear

Bellcrank Spacer: 1.5 mm

Rear Suspension

Shock stay high: 0.5
 Spacer: 2 mm
 Shock Stay:
 LA217(SP)
 LA217H

Wing Height: _____
 Camber Angle: 1.5 °
 Sway Bar: 1.2 (RED)

Sus. Holder (RF):
 IN OUT B

Sus. Holder (RR):
 IN OUT E

Ride Height: 21 mm

Sus. Holder Spacer:
 Front
 Rear

Spacer: 2 mm
 Wheel Spacer: 1 mm
 Hub Spacer:
 F: 0.5 mm
 R: 1.5 mm

Rear Sus. Arm:
 LA272(UM566,UM521)(SP)
 UM521-1(1-Hole)
 LA255

Rear Hub and Toe:
 0°Type-B(UM519)
 0°Type-B2(UM516-2)
 0°Alu(UMW516-0)
 0.5°Alu(UMW516-05)
 1°Alu(UMW516-1)

Shock

	Front	Rear
Shock Piston:	<u>5 Hole</u>	<u>5 Hole</u>
Shock Oil:	<u># 42.5 (X-gear)</u>	<u># 37.5 (X-gear)</u>
Shock Spring:	<u>Red</u>	<u>Red</u>
Limiters:	in mm <u> </u> out 1 mm	in mm <u> </u> out 1 mm
Shock Length (A):	<u>20.5</u> mm	<u>27.5</u> mm
Shock Top Type:	<input type="checkbox"/> <input checked="" type="checkbox"/>	<input type="checkbox"/> <input checked="" type="checkbox"/>
5.8mm Ball End:	Front: <input type="checkbox"/> S <input checked="" type="checkbox"/> M <input type="checkbox"/> L	Rear: <input type="checkbox"/> S <input type="checkbox"/> M <input checked="" type="checkbox"/> L

Kind in spring

Soft	Pink
	White
	Gold
	Red
	Yellow
	Orange
Hard	Green

Sway Bar

1.0	White
1.1	Pink
1.2	Red
1.3	Orange
1.4	Yellow
1.5	Blue
1.6	Green

Tire

	Front	Rear
Tire:	<u>Panther Cry</u>	<u>Panther Cry</u>
Inserts:	<u>Std</u>	<u>Std</u>
Wheel:	<u>Std</u>	<u>Std</u>
Traction Compound:	_____	_____

Body/Wing/Other

Body: Bull dog

Wing: Step S

Lip hight: 7mm

Wing Angle:
 4° 7° 10°

Battery Post:
 Pla Alu

Slipper Type:
 Direct
 Separates

Slipper Sheet (F-R):
 Red-White
 Red-Red
 White-White

Center Post:
 Pla Alu

Back bone screw:
 F R

Comments

Use NCG sus arm. (LAW43)

Electronics

Motor: Peak 6.5T

Pinion/Spur: 18/78

Battery: Peak 4500

ESC: Much More FLETA

Radio: Futaba 4PK super

Servo: BLS 551

Throttle/Brake:
 EPA: Expo:

Initial brake: 0%

Drag brake: 9%

Throttle profile: 1

Steering expo: _____

Steering speed: _____

<input checked="" type="checkbox"/> Smooth	<input type="checkbox"/> Sandy
<input type="checkbox"/> Bumpy	<input type="checkbox"/> Soft Dirt
<input type="checkbox"/> Low Traction	<input type="checkbox"/> Grass
<input type="checkbox"/> Med. Traction	<input type="checkbox"/> wet
<input checked="" type="checkbox"/> Higt Traction	<input type="checkbox"/> Dry
<input type="checkbox"/> Blue Groore	<input type="checkbox"/> Dusty
<input checked="" type="checkbox"/> Clay	<input type="checkbox"/> Other