

Name: Jared Tebo Date: Jan 2013 Truck / City: WCRC Event: Reedy

Front Suspension

4.8mm Ball Stud: **Camber:** 1°
 UM128 (Std) UMW508 (+2mm High Mount)

Upper Spacer: 1 mm

4.8mm Ball Stud Spacer: 1 mm

4.8mm Ball Stud: **Ackerman Steer Spacer:** 1 mm
 LA246 (-1mm Low Mount) UM129 (Std)

Axle Spacer: Out ___ mm In ___ mm

Wheel Hub: ___ mm

Bump Steer Spacer: 0 mm

Toe: In Out 0°

Front Bulkhead Weight Placement:
 None
 Bulkhead Inside ___ oz ___ g
 On the skid plate ___ oz ___ g * 1oz=28g

Caster: 25° 30°
 A (UM502) B (UM721/Std.) C (UM567)

Spacer: 0.5 1.0 None

Caster Block: 0° 2° 4°

Block position: IN OUT

Axle Height Spacer: ___ mm 1.5 mm

Wheelbase: F: ___ mm R: 1 mm

Comments: RB5 axle UM506/LAW30GM

Rear Suspension

Sus Holder Spacer: F 0.5 1.0 None R 0.5 1.0 None

Anti-Squat: 0°

Upper Spacer: 1 mm

4.8mm Ball Stud: UM129 (Std) UMW508 (+2mm High Mount) 97050M

Sway Bar: None ___ mm

Camber: 1°

Wheelbase: F: ___ mm R: ___ mm

RR: 2 mm

Lower Sus Holder: Normal RF Aluminum(Opt) UMW511+UMW512 UMW514+UMW515
 Narrow Wide RF2

Upper Spacer: 2 mm

Mid: 1 mm

Wheelbase: F: 1 mm R: 1 mm

Rear Hub add Toe: 0°Type-B (UM519) 0°Type-B2 (UM519-2) 0°Alu (UMW516-0) 0.5°Alu (UMW516-05) 1°Alu (UMW516-1)

Axle Spacer: Out ___ mm In ___ mm

Motor Position: Rear Motor Midship Motor

Diff.: Gear Diff. # ___ Ball Diff.

Comments: UM521-1 Rear arms

Shock

Shock Piston: Front 4 X 55 Rear 4 X 55

Shock Oil: # 35 # 27.5

Shock Spring: Pink White

Limiters: in out mm in out 1 mm mm

Shock Length(A): ___ mm ___ mm

Shock Length(B): 20 mm 27 mm

Shock Length(C): ___ mm ___ mm

Ball End type: Front: S M L Rear: S M L

Chassis

Screw:

Ride Height: F 24 mm R 23 mm

Battery Position

Battery Type: Straight Separate Short

Battery Placement: Front Rear

Truck Condition

Smooth Sandy Bumpy Soft Dirt Low Truction Grass Med. Truction Blue Groove Higt Truction Clay Wet Dusty Dry Other

Wing

Blast-S Wing Mount: Narrow Wide Blast-L Step-S Step-M Step-L Step 2.0 Lip: 13mm

Wing Angle: 4° 7° 10°

Tire

Front: Hand Out Rear: Hand Out

Inserts: Hand Out

Wheel: AKA AKA

Traction Compound: ___

Electronics

Motor: Orion 7.5

Pinion/Spur: 21/76

Battery: Orion 4000

ESC: Orion R10

Comment

KO RSx Response Servo. Th. EPA 100/65

ESC 10% drag / 5 power