

Name: Jared Tebo Date: January 2014 Truck / City: Ohio RC Factory Event: 2014 CRCRC

Front Suspension

Upper Spacer: 1 mm

4.8mm Ball Stud: Camber: 2 °

UM128 (Std) UMW508 (+2mm High Mount)

Axle Spacer: Out mm In mm

4.8mm Ball Stud Spacer: 1 mm

Wheel Hub: mm

Ackerman Steer Spacer: 0 mm

Bump Steer Spacer: 0 mm

Toe: In Out 0 °

Tie Rod:

Front Bulkhead Weight Placement: None Bulkhead Inside oz g On the skid plate oz g * 1oz=28g

Caster: 25° 30°

Spacer: 0.5 1.0 None

Caster Block: 0° 2° 4°

Caster Block position: IN (wide/Std) OUT (Narrow)

Axle Height Spacer: mm 1.5 mm

Wheelbase: F: 1 mm R: 0 mm

Comments: Ackermann Arrow Pointing Back

Rear Suspension

Sus Holder Spacer: F 0.5 1.0 None R 0.5 1.0 None

Anti-Squat: °

4.8mm Ball Stud: UM129 UMW508 (+2mm High Mount) 97050M UM128 (Std)

Sway Bar: None mm

Upper Spacer: 1 mm

Lower Sus Holder: Normal RF Aluminum (Opt) UMW511+UMW512 UMW514+UMW515

Universal Swing Shaft: 65.5

Camber: 2 °

Upper Spacer: 1 mm

Wheelbase: F: 0 mm R: 2 mm

Wheelbase: F: mm R: mm

Rear Hub add Toe: 0° Type-B (UM519) 0° Type-B2 (UM519-2) 0° Alu (UMW516-0) 0.5° Alu (UMW516-05) 1° Alu (UMW516-1)

Axle Spacer: Out mm In mm

RR: Mid:

Comments: UMW705/707 A/B Out UM521-1 arms used

Motor Position

Rear Motor Midship Motor

Diff.

Gear Diff. # Ball Diff.

Shock

Shock Piston: Front Drilled 4X1.3 Rear Drilled 4X1.3

Shock Oil: # 35 # 30

Shock Spring: Pink Gold

Limiters: in out mm in out mm

Shock Length (A): mm mm

Shock Length (B): 20 mm 27 mm

O-ring: ORG03X ORG03X

Ball End type Front: S M L Rear: S M L

Battery Placement:

None Screw Front Rear

Foam: Front Rear None

Servo/small gap/battery/speedo

Battery Type

Straight Separate Short

Type: Orion 4000

Chassis

F 24 mm Ride Height: R 24.5 mm

Other

Motor: Orion VST2 7.5

ESC: Orion R10 Pro

Pinion/Spur: 21/76

Tire

Front: AKA Typo Clay Rear: AKA Typo Clay Traction Compound or comment: Buggy Grip

Inserts: Red Evo Red Evo

Wheel: Evo Evo

Comment

All Lunsford titanium screws. Chassis tape. RSx servo

Truck Condition

Smooth Sandy Low Truction Grass Med. Truction Blue Groove Higt Truction Clay Wet Dry Other

Wing

Blast-S Wing Mount : Blast-L Narrow Step-S Wide Step-M Wing Angle : Step-L Step 2.0 4° 7° 10°

Lip : Middle line