

Name: Cody Turner Date: Oct. 2013 Truck / City: Hot Rod Hobbies Event: Reedy Truck Race

Front Suspension:

4.8mm Ball Stud: UM128 UMW508 (+2mm High Mount)

Upper Spacer: 2 mm

Shock Mount: IN OUT

Camber: 1.5°

Ackerman Steer Spacer: 1 mm

Bump Steer Spacer: 1 mm

Upper Spacer: 0 mm

Toe: In Out 0 °

Sus Mount: UM502 UM567 UM721 (Std)

30 52

Caster: 25° 30° None

Spacer: 0.5 1.0 None

Axle Spacer: Out 1 mm In

Caster Block: IN (wide/Std) OUT (Narrow)

Axle Height Spacer: Up Down

Wheelbase: Long Middle Short

4.8mm Ball Stud: LA246 (-1mm Low Mount) 97050M

Comments: _____

Rear Suspension:

Sus Holder Spacer: F 0.5 1.0 None R 0.5 1.0 None

Upper Spacer: 2 mm

Wheelbase: F: 4 mm R: 2 mm

Anti-Squat: 0 °

Sway Bar: None _____ mm

Type-B (UM519) Type-B2 (UM519-2)

Camber: 1.5°

Rear Hub: 0° Type-B (UM519) 0° Type-B2 (UM519-2) 0° Alu (UMW704-0) 0.5° Alu (UMW704-05) 1° Alu (UMW704-1)

Lower Sus Holder: Normal Aluminum(Opt) RF RF2 Front _____ Rear _____

Axle Spacer: Out 1 mm In 1 mm

Upper Spacer: 1 mm

Comments: **UMW511/512GM Used**

Drive: Rear Motor Midship Motor

Diff: Gear Diff # _____ Ball Diff **Snug**

Shock:

| | Front | Rear |
|------------------|--|---|
| Shock Piston: | Std 5h | Std 5h |
| Shock Oil: | # 37.5 | # 32.5 |
| Shock Spring: | Red | Gold |
| Limiters: | in out mm mm | in out mm mm |
| Shock Length(A): | <u>26</u> mm | <u>33</u> mm |
| Shock Top Type: | <input checked="" type="checkbox"/> Normal <input type="checkbox"/> Alu(UM719) | |
| 5.8mm Ball End: | Front: <input checked="" type="checkbox"/> S <input type="checkbox"/> M <input type="checkbox"/> L | Rear: <input type="checkbox"/> S <input checked="" type="checkbox"/> M <input type="checkbox"/> L |

Chassis:

Weight Placement:

F 30 mm Ride Height: R 28 mm

Tire: Front PL Ion Rear PL Ion


Inserts: PL 2 Stage

Wheel: Kyosho Kyosho

Traction Compound: X2 Tire compound

Comment: _____

Battery Placement:



Electronics:

Motor: **Orion VST2 6.5**

Pinion/Spur: 19/80

Battery: **Orion Shorty**

ESC: **Orion R10 Pro**

Radio: **Airtronics M12**

Servo: **Orion VDS2**

Throttle/Brake: _____

E PA: 100/95 Expo: 0

Initial brake: **Drag Brake**

Drag brake: 8%

Throttle profile: 5

Steering expo: 0

Steering speed: 0

Body:

PL Bulldog for T4.2

Material:

Screw: Steel Titanium

Servo Horn: Normal Rigid(UM717)

Pinion Gear: Steel Aluminium

Shock Ring: O-ring X-ring Red Clear