

Name: Jared Tebo Date: January 2014 Truck / City: Ohio RC Factory Event: 2014 CRCRC

Front Suspension:

4.8mm Ball Stud:
 UM128
 UMW508 (+2mm High Mount)

Upper Spacer: _____ mm

Shock Mount:
 IN
 OUT

Camber: 2°

Ackerman Steer Spacer: 0 mm

Bump Steer Spacer: 0 mm

Upper Spacer: 1 mm

Toe: In Out 0°

Sus Mount:
 UM502
 UM567
 UM721

Caster:
 25°
 30°
 None

Spacer:
 0.5
 1.0
 None

Axle Spacer:
 Out _____ mm
 0°

Caster Block:
 IN (wide/Std)
 OUT (Narrow)

Wheelbase: Long Middle Short

4.8mm Ball Stud:
 LA246 (-1mm Low Mount)
 97050M

Axle Height Spacer:
 Up
 Down

Comments: Ackermann arrow pointing back

Rear Suspension:

Sus Holder Spacer:
 F 0.5 1.0 None
 R 0.5 1.0 None

Upper Spacer: 2 mm

Wheelbase:
 F: 2 mm
 R: 4 mm

Anti-Squat: _____°

Sway Bar: None _____ mm

Camber: 2°

Lower Sus Holder:
 Normal RF RF2
 Aluminum(Opt) Front C in Rear B in

Upper Spacer: 1 mm

Comments:

Drive:
 Rear Motor
 Midship Motor

Diff:
 Gear Diff # _____
 Ball Diff

Rear Hub:
 0° Type-B (UM519)
 0° Type-B2 (UM519-2)
 0° Alu (UMW704-0)
 0.5° Alu (UMW704-05)
 1° Alu (UMW704-1)

Axle Spacer:
 Out _____ mm
 In _____ mm

Shock:

	Front	Rear
Shock Piston:	Drilled 4X1.3	Drilled 4X1.3
Shock Oil:	# <u>35</u>	# <u>30</u>
Shock Spring:	<u>Red</u>	<u>Red</u>
Limiters:	in out mm mm	in out mm mm
Shock Length(A):	<u>25.5</u> mm	<u>33</u> mm
Shock Top Type:	<input type="checkbox"/> Normal	<input checked="" type="checkbox"/> Alu(UM719)
5.8mm Ball End:	Front: <input checked="" type="checkbox"/> S <input type="checkbox"/> M <input type="checkbox"/> L	Rear: <input type="checkbox"/> S <input checked="" type="checkbox"/> M <input type="checkbox"/> L

Chassis:

Weight Placement:
 Servo / Receiver / Battery / Speedo

F 30 mm Ride Height: R 28 mm


Tire: Front AKA Typo Clay Rear AKA Typo Clay

Inserts: AKA Red AKA Red

Wheel: Kyosho Kyosho

Traction Compound: Buggy Grip

Battery Placement:



Electronics:

Motor: OrionVST2 6.5
 Pinion/Spur: 18/82
 Battery: Orion 5500 Saddle
 ESC: Orion R10 Pro
 Radio: KO EX-1
 Servo: KO RSx Response
 Throttle/Brake:
 E PA: 100/80 Expo: _____
 Initial brake: Drag
 Drag brake: 7
 Throttle profile: 5
 Steering expo: _____
 Steering speed: _____

Body:

JC Finisher

Material:

Screw: Steel Titanium
 Servo Horn: Normal Rigid(UM717)
 Pinion Gear: Steel Aluminium
 Shock Ring: O-ring X-ring Red Clear

Comment: Chassis Tape