

Name \_\_\_\_\_ Date \_\_\_\_\_ Truck / City \_\_\_\_\_ Event \_\_\_\_\_

### Front Suspension:

**4.8mm Ball Stud:**  
 UM128  
 UMW508 (+2mm High Mount)

**Upper Spacer:** \_\_\_\_\_ mm

**Shock Mount:**  
 IN  
 OUT

**Axle Spacer:**  
 Out \_\_\_\_\_ mm

**Caster Block:**  
 IN (wide/Std)  
 OUT (Narrow)

**4.8mm Ball Stud:**  
 LA246 (-1mm Low Mount)  
 97050M

**Ackerman Steer Spacer:** \_\_\_\_\_ mm

**Bump Steer Spacer:** \_\_\_\_\_ mm

**Axle Height Spacer:**  
 Up  
 Down

**Toe:**  In  Out \_\_\_\_\_ °

**Sus Mount:**  
 UM502  
 UM567  
 UM721

**Caster:**  
 25°  
 30°

**Spacer:**  
 0.5  
 1.0  
 None

**Wheelbase:**  Long  Middle  Short

Comments: \_\_\_\_\_

### Rear Suspension:

**Sus Holder Spacer:**  
 F  0.5  1.0  None  
 R  0.5  1.0  None

**Anti-Squat:** \_\_\_\_\_ °

**Sway Bar:**  None  \_\_\_\_\_ mm

**Upper Spacer:** \_\_\_\_\_ mm

**Wheelbase:**  
 F: \_\_\_\_\_ mm  
 R: \_\_\_\_\_ mm

**Rear Hub:**  
 0° Type-B (UM519)  
 0° Type-B2 (UM519-2)  
 0° Alu (UMW704-0)  
 0.5° Alu (UMW704-05)  
 1° Alu (UMW704-1)

**Lower Sus Holder:**  
 Normal Aluminum(Opt)  
 RF  RF2 Front \_\_\_\_\_ Rear \_\_\_\_\_

**Upper Spacer:** \_\_\_\_\_ mm

Comments: \_\_\_\_\_

**Drive:**  
 Rear Motor  
 Midship Motor

**Diff:**  
 Gear Diff # \_\_\_\_\_  
 Ball Diff \_\_\_\_\_

### Shock:

	Front		Rear	
Shock Piston:	_____		_____	
Shock Oil:	# _____		# _____	
Shock Spring:	_____		_____	
Limiters:	in	mm	in	mm
	out	mm	out	mm
Shock Length(A):	_____ mm		_____ mm	
Shock Top Type:	<input type="checkbox"/> Normal		<input type="checkbox"/> Alu(UM719)	
5.8mm Ball End:	Front:	<input type="checkbox"/> S <input type="checkbox"/> M <input type="checkbox"/> L	Rear:	<input type="checkbox"/> S <input type="checkbox"/> M <input type="checkbox"/> L

### Chassis:

**Battery Placement:** Front Rear

**Weight Placement:**  
 No Screw  
 Screw

F \_\_\_\_\_ mm Ride Height: R \_\_\_\_\_ mm

**Tire:** Front \_\_\_\_\_ Rear \_\_\_\_\_

Tire: \_\_\_\_\_  
 Inserts: \_\_\_\_\_  
 Wheel: \_\_\_\_\_  
 Traction Compound: \_\_\_\_\_

### Track Conditions:

Composition: \_\_\_\_\_  
 Surface: \_\_\_\_\_  
 Traction: \_\_\_\_\_  
 Comments: \_\_\_\_\_

### Electronics:

Motor: \_\_\_\_\_  
 Pinion/Spur: \_\_\_\_\_  
 Battery: \_\_\_\_\_  
 ESC: \_\_\_\_\_  
 Radio: \_\_\_\_\_  
 Servo: \_\_\_\_\_  
 Throttle/Brake: \_\_\_\_\_  
 E PA: \_\_\_\_\_ Expo: \_\_\_\_\_  
 Initial brake: \_\_\_\_\_  
 Drag brake: \_\_\_\_\_  
 Throttle profile: \_\_\_\_\_  
 Steering expo: \_\_\_\_\_  
 Steering speed: \_\_\_\_\_

### Body:

### Material:

Screw:  Steel  Titanium  
 Servo Horn:  Normal  Rigid(UM717)  
 Pinion Gear:  Steel  Aluminium  
 Shock Ring:  O-ring  X-ring  Red  Clear

Comment: \_\_\_\_\_  
 \_\_\_\_\_  
 \_\_\_\_\_